



## Hi Cure UV Dryer

Also available in versions for **Opaque white curing** and as **Low Energy** version for high reactive inks

### System features

- High radiation performance and energy efficiency
- Ultra-compact and light weight design
- Plug & Play connections

### advantages

- High level of performance also for demanding processes
- High reliability and adaptability
- Service friendly
- Plug & Play lamp change

## New highlights in industrial printing with UV colours

UV colours enable a quicker printing process, higher shine and a range of design possibilities, depending on the corresponding UV hardening. An example is the new Eltosch-Grafix HiCure UV Dryer.

- Approx. 30 % improved efficiency, with corresponding energy savings
- easy to use, such as plug connections for lamp changing
- cold radiation environment also enables the use of heat-sensitive printing substrates

Performance is an easy equation with the HiCure UV dryer: The significantly higher efficiency either allows to increase the printing speed or to reduce the energy consumption. The efficient water cooling system (approx. 50 % cooling power) also enables energy savings and stable performance. As a result, the life-span of the UV lamps increases. In turn, high UV-C production also guarantees quick, reliable drying.

### Through optimal collimating,

new reflector and lamp geometry ensures highly-efficient radiation production and even drying. In addition to this, the high and well distributed cool water flow in the reflector and shutter guarantees the longevity of the whole system. Other advantages are offered by the sturdy design with practically no expendable parts and an easy-to-maintain structure. Reflector plates and shutters can be replaced separately. The automatic shutter closure function in stand-by mode ensures maximum safety.

Easy-to-use system ensures safety and reliability



The new Hi-Cure UV Dryer makes life easy for operators. The device is operated via the control panel or convenient G66-Touch! Screen. Questions concerning functions are answered via remote maintenance – even with the machine in operation. The practical replacement cassette enables the flexible use of the UV module. Another practical feature: The UV lamps can be changed quickly and easily via plug connection – no tools necessary!

hönle group		Drying	Powder	Curing	Cooling	Service
aladin	eleco-efd	eltosch grafix	hönle	panacol	printconcept	raesch
		tangent	uv-technik speziallampen			



Eltosch Grafix GmbH, Fahltskamp 64, 25421 Pinneberg, Germany  
Phone: +49 4101 5150 700, Fax: +49 4101 / 5150 729. [www.eltosch-grafix.com](http://www.eltosch-grafix.com)

Operating parameters depend on production characteristics and may differ from the foregoing information. We reserve the right to modify technical data. © Copyright Eltosch Grafix GmbH. Updated 04/16.